# PAR/////NER

CARE . TRUST . RESPONSIBILITY

# Order Terminal OT-200
## The new dimension of ordering

The functionality and stylish appearance of the OT-200 is primarily designed to the hospitality environment. It has a compact size, lightweight design and a high durability.

Orders can be transmitted directly from the OT-200 to the bar or kitchen via WiFi i.e. employees work more efficient instead of walking back and forth.

The OT-200 is a cost effective handheld terminal, which will enhance any hospitality solution and can be used in many other business environments as well.

## Special Features

Stylish and compact

Lightweight design

Large 4.3'' widescreen touch LCD

Windows™ Mobile 6.5 Professional

WLAN, bluetooth

Ruggedized to IP54 and 1.2m drop test

## Optionen

MSR

RFID 13.56 MHz (MIFARE)

Scanner 1D Symbol SE955

Scanner 2D Honeywell

## Technical data

| Item | OT-200 |
|------|--------|
| CPU | Samsung S3C6410 667MHz |
| Memory | 256MB NAND Flash, 256MB SDRAM |
| Operating System | Microsoft Windows™ Mobile 6.5 Professional |
| LCD | 4.3" TFT LCD touchscreen (widescreen 480 x 800) |
| I/O Interface | WiFi 802.11b/g, Bluetooth 2.0 Class II compatible, Mini-USB 2.0 |
| Audio | Speaker, earphone jack (3.5mm), microphone jack (2.5mm), Internal microphone |
| Extensions | MicroSD memory socket, supports SDHC up to 16GB |
| Ruggedness | Drop test: 1.2 meters, IP54 |
| Environment | Temperature — Operating 0~40 ° C, Storage -20~60 ° C |
| Dimensions | 82 mm (W) x 133 mm (L) x 19 mm (H) |
| Weight | Approx. 245g with battery |
| Battery | Rechargeable Li-ion battery 2200mAh (removable) |
| Power Supply | 5V 2A |
| Special features | Vibration buzzer, 4-way directional sensor, ambient light sensor |
| Certification | RF: FCC, CE, SRRC, NCC<br>EMC: FCC, CE, BSMI, VCCI<br>Safety: BSMI, CB |
| Accessories | AC Adapter, second battery, high quality stylus, stylus cord, hand strap, leather pouch, leather pouch cord, shoulder strap, carry bag (also for OT with scanner or add-on RFID) cradle, multicradle |
| Options | 3-track MSR, RFID 13.56MHz (MIFARE), barcode scanner module (1D & 2D) |



Add-on RFID module



Add-on MSR module



Print orders directly to
MP-300 mobile printer via Bluetooth



Cradle with spare battery
charging slot



Packed with
comprehensive accessoires



Carry bag with shoulder strap and flipping cover
for standard OT-200 as well as for OT-200 with RFID
module or Scanner for highest protection

Subject to alterations June 2013