



CARE . TRUST . RESPONSIBILITY

EM-70 7" Android Enterprise Tablet



Smoothing Your Business EM-70 Features

- Latest ARM technology for high performance
- Android 4.2 Operating System
- Auto rotating display (portrait or landscape)
- Light weight and stylish design
- Dust and spill resistant

Optional

- Cradle for holding and charging
- NFC 13.56MHz
- IC Card reader
- 3-track MSR
- 1D/2D barcode reader

EM-70 Enterprise Tablet, Smoothing Your Business

The EM-70 is a stylish enterprise tablet designed to guarantee you the satisfaction with durability and profitability. It equips the latest technology to ensure a high processing performance for its users and build with Android 4.2 to ensure flexibility in any applications. It combines with different features, such as wireless communication, IP54 protection class, long last working power design, and quality accessories as cradle, IC Card reader, MSR and 1D/2D barcode reader to choose.

EM-70 has the highest usability with industrial needs for all kinds of applications in retail, restaurant, logistics and in field, EM-70 is the best helper in smoothing your business.

Item	EM-70
Processor	Freescale i.MX 6 1G
OS	Android 4.2
Memory	Standard: 1GB
Storage	Standard: 8GB
Display	7", 1024x 600, 350nits
Capacitive Touch	Capacitive touch
WWAN (option)	For data , GPRS/EDGE/WCDMA/850/900/1800/1900/2100
WiFi	802.11 a/b/g/n
Bluetooth	V4.0+HS
GPS (option)	Stand Alone & AGPS (Support Glonass)
Back Camera	CMOS, 5.0 Mega Pixels, flash light
Battery	Rechargeable Li-ion battery 3.7V, 6000mAh
Speaker	Internal, 1 (0.8W)
I/O	1 x SIM (Internal) 1 x Micro SD 1 x DC Jack 1 x Earphone Jack 1 x Micro USB female type, OTG & charging function 1 x Power button, 2 x Volume button 1 x POGO Pins (for Cradle), include DC charging function
LEDs	1 x Red/Green LED for power & system status
Power Adaptor	Input:100V to 240V AC 50/60Hz 0.5A Output: 5V DC 3A; AC cable
Dimension	219.4mm x 141.3mm x 22.3mm
Operating temperature	0°C to +40°C
Storage temperature	-20°C to +60°C (without battery)
Humidity	5% to 95% RH (no condensation)
Sealing	IP65
Drop specification	1.2M (Device Only)
Option Device Module (Factory Option)	IC card reader ISO7816 RFID (NFC) 13.56MHz, ISO 14443 A/B, Felica
Optional Module	1D barcode scanner (laser) or 2D barcode scanner (image) MSR ISO7811-Track 1.2.3
Certification	CE / FCC / VCCI / CCC / BSMI
Cradle (option)	Charging the EM-70 device Factory option with 1 battery or w/o battery (6000mAh) 1 x USB Type A 1 x DC IN connector


* specification subject to change without prior notice



7" High Brightness Equipped with Auto Rotation Function



Integrated MSR / Barcode Reader (optional)



EM-70 in Cradle



Cradle of EM-70 (optional)



Various I/O



Power & Volume-Buttons



Integrated IC Card Reader (optional)



CARE . TRUST . RESPONSIBILITY

Partner Tech Corporation

Taiwan	TEL:+886-2-29188500	FAX: +886-2-29153405	E-mail:sales@partner.com.tw
USA	TEL:+1-949-598-1888	FAX: +1-949-598-0088	E-mail:sales@partnertechcorp.com
Europe	TEL:+49 (0)40 450 635-0	FAX:+49 (0)40 450 635-130	E-mail:info@partner-tech.eu
UK	TEL:+44 (0)1928 579 707	FAX:+44 (0)1928 571 308	E-mail:sales@partnertechuk.com
China	TEL:+86-21-67696667	FAX: +86-21-67696699	E-mail:sales@partnertech.com.cn
Africa	TEL:+27-11-700-7188	FAX:+27-11-700-7140	E-mail:sales@partnertech.co.za
Middle East	TEL:+971-4-8862980	FAX:+971-4-8862980	E-mail:sales@partnertechme.com
Korea	TEL:+82-10-6404-8223	I-Phone:+82-70-4104-8223	E-mail:adams_c@partner.com.tw

